

# EPIGAP Optronics GmbH

Koepenicker Str. 325b  
 D-12555 Berlin  
 Fon: +49 (0)30 657637 60  
 Fax: +49 (0)30 657637 70  
 sales@epigap-optronic.de



## Data sheet

page 1 of 2

### Infrared LED

### EOLD-1200-015

Rev. 02, 2017

Radiation	Type	Case
Infrared	InGaAs/InP, MQW	TO-46 with glass lens cap

	Description:
<p style="text-align: center;">① Cathode      ② Anode</p> <p style="text-align: center;">Dimensions (Unit:mm)</p>	Application:
	<p>High-power, high speed, narrow beam angle, high reliability</p> <p>Optical switches, optical communication, safety equipment, automation</p>

### Maximum Ratings

T<sub>amb</sub> = 25°C, unless otherwise specified

Parameter	Test conditions	Symbol	Value	Unit
Forward current		I <sub>F</sub>	100	mA
Peak forward current (pulse)	t ≤ 50 μs, T = 100 μs	I <sub>FM</sub>	200	mA
Reverse voltage	I <sub>R</sub> = 10 μA	I <sub>FM</sub>	5	V
Power dissipation		P <sub>D</sub>	115	mW
Operating temperature range		T <sub>amb</sub>	-20 to +85	°C
Storage temperature range		T <sub>stg</sub>	-30 to +100	°C
Lead soldering temperature	t < 5 s, 3 mm from case	T <sub>slg</sub>	260	°C
Junction temperature		T <sub>J</sub>	100	°C



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

# EPIGAP Optronic GmbH

Koepenicker Str. 325b  
D-12555 Berlin  
Fon: +49 (0)30 657637 60  
Fax: +49 (0)30 657637 70  
sales@epigap-optronic.de



## Data sheet

page 2 of 2

## Infrared LED


## EOLD-1200-015

Rev. 02, 2017

### Optical and Electrical Characteristics

$T_{amb} = 25^{\circ}\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	$V_F$	$I_F = 20\text{ mA}$		0.9	1.0	V
Forward voltage	$V_F$	$I_F = 100\text{ mA}$		1.0	1.2	V
Radiant power	$\Phi_e$	$I_F = 20\text{ mA}$	1.1	1.5		mW
Radiant power	$\Phi_e$	$I_F = 100\text{ mA}$		7		mW
Peak wavelength	$\lambda_p$	$I_F = 20\text{ mA}$	1170	1200	1230	nm
FWHM	$\Delta\lambda_{0,5}$	$I_F = 20\text{ mA}$		70		nm
Viewing angle	$\varphi$	$I_F = 20\text{ mA}$		6		deg.
Switching times	$t_r, t_f$	$I_F = 20\text{ mA}$		25; 40		ns



Typical radiation pattern

Art. No. 430 077



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.